



PCB Layout Diagram
Top View

NOTE:
 1.MATERIAL:
 a.HOUSING:THERMOPLASTIC GLASS FIBRE UL94V-0
 b.CONTACT:PHOSPHOR BRONZE
 (SURFACE PLATING:A*U*)
 SEE ORDERING INFORMATION
 2.ELECTRIC:
 a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
 b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 d.OPERATING TEMPERATURE: -25°C~ +85°C

ORDERING INFORMATION

BS-12-B***003

電池座系列
 BS-12系列
 SMT 180° TYPE

PLATING:
 A-Au1U"
 J-Ni100U"
 K-SNI100U"
 K-SNI120U"

MATERIAL:
 1A-PBT BLACK
 1B-PA66 BLACK
 2A-PPA BROWN
 2B-PPA BLACK
 3A-PPS BROWN
 3B-PPS BLACK
 4A-LCP WHITE
 4B-LCP BLACK

REV.	ECN NO.	REVISED	DATE

UNLESS OTHERWISE SPECIFIED TOLERANCES	SCALE: 1:1	SIZE: A4	VIEW:	PART NO:
DECIMALS: X ±0.30 X ±1°	UNIT: mm	REV.: A/O	OBJECT: QJ	CR1220-ZZX
X.X ±0.25 X.X ±0.5°	audit	QJ.LIU	DATE	TITLE:
X.XX ±0.20 X.XX ±0.10	Design	QJ.HUAN	DATE	QJ-1220-ZZX-SMT
WEIGHT: 0.6 g	Drawing	QJ.LIU	DATE	
SHEET 1 OF 1				

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.20MM	Gold Plating and Ni Under-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.20MM	Gold Plating and Ni Under-Plating
1	HOUSING	1	PPS	BROWN
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR